

*Bergen*

**BYGGINNREDNING AS**

## GLASSTYPER.

TYPE GLASS	TYKKELSE	RwdB	Motstandsklasse
HERDET	4MM	29	1C1
HERDET	6MM	31	1C2
HERDET	8MM	32	1C2
HERDET	10MM	33	1C1
HERDET	12MM	34	1C1
LAMINERT	6,4MM	32	2B2 P1A
LAMINERT	6,8MM	32	1B1 P2A
LAMINERT	8,8MM	33	1B1 P2A
LAMINERT	10,8MM	34	1B1 P2A
LAMINERT	12,8MM	37	1B1 P2A
LAMINERT	16,8MM	38	1B1 P2A
LYDLAMINERT	6,8MM	36	1B1 P2A
LYDLAMINERT	8,8MM	37	1B1 P2A
LYDLAMINERT	10,8MM	38	1B1 P2A
LYDLAMINERT	12,8MM	40	1B1 P2A
LYDLAMINERT	16,8MM	41	1B1 P2A
BRANGLASS EW30	11MM	37	1B1 P1A
BRANGLASS EI30	15MM	38	2B2 P1A
BRANGLASS EI60	23MM	41	1B1 P1A
ISOLERGLASS	35MM	44	1C1-1B1
ISOLERGLASS	42MM	49	1B1
ISOLERGLASS	52MM	52	1B1 P2A

**OPPGITTE VERDIER ER BASERT PÅ  
GLASS TESTET I KARM 1230\*1530MM  
UNDER OPTIMALE FORHOLD.**